

PUBLIC TELEPHONE SIGNS
GLADWIN AND CASCADE
PLASTIC SIGNS

Description and Installation

1. GENERAL

1.01 This appendix covers the description and installation of Gladwin and Cascade plastic telephone signs.

2. DESCRIPTION

2.01 The Gladwin T-306 consists of a 30" x 5" piece of black plastic with the word telephone in flame color. The T-306-A is a flame colored plastic arrow for attaching to the T-306 sign.

2.02 The Cascade T-1 consists of an 18" x 5" piece of blue plastic with the word telephone and reversible arrows made of white plastic on both sides. A metal end bracket is provided for vertical mounting. The T-2 is the same as the T-1 except the word telephone and the arrow are on one side only. The T-3 has the word telephone on one side only.

3. INSTALLATION

3.01 With the exception of the Cascade T-1 all are intended for use on a vertical surface. Mounting holes on the

T-306 are positioned on 18" centers. If the sign is attached to plastic surface and the studs are on 16" centers, move one of the upper mounting holes to allow 16" center.

3.02 Where possible enlarge the mounting holes and use a No. 6 blued round head wood screw.

3.03 For locations using toggle bolts paint head of bolt black.

3.04 When drilling or countersinking, place the sign on a wooden surface as a precaution against cracking or breaking.

3.05 The Cascade T-1 should be attached to a vertical surface using the brackets provided.

3.06 In attaching the T-306A to the T-306 the mounting holes on the rear of the T-306 should be drilled and countersunk to take a 6-32 flat head machine screw.