



Loudspeaking Intercommunication System AVF 404

Master Station CENTRUM DEE 15001



Loudspeaking master station for Intercom System AVF 404.

The station has a grey impact-resistant plastic cover and is designed to be placed on a desk, but can also be wall-mounted. It can be connected to all AVF 404 automatic exchanges.

The primary function of the AVF 404 system is to provide loudspeaking speech communication; voice-operated speech direction control grants hands-free conversation. A potentiometer, adjustable through the base plate, matches the station to prevailing rooms acoustics. In consequence of this feature the talk button need not be used except in cases of high noise level close to the station.

The station is equipped with a directory plate which can be drawn out from underneath the base plate.

The master station is also available with handset for confidential conversations (DEE 15101).



Master station with handset DEE 15101

SUPPLEMENTARY EQUIPMENT

The master stations can be provided with extra devices for the following facilities:

Extra call signal

By relay box BCV 90101 an extra call signal can be received through an external signalling device consisting of a loud-speaker, a buzzer or a bell. The external signalling device can also comprise a call indication lamp. The extra call signal is disconnected as the call is accepted.

Party-line

Via relay box KFB 16104, two stations can be connected to **one** line. Outgoing calls are made in usual fashion from both stations. Incoming calls are connected to the last time used station. A call in progress can be switched back and forth between the stations. Adding relay box BCV 90101, all incoming calls can **either** be distributed to one of the stations only, **or** be indicated on both.

A combination of two or more KFB 16104 boxes makes it possible to connect an equivalent number of stations to the same line.

MECHANICAL DATA

Height	115 mm (4 ¹⁷ / ₃₂ ")
Width	233 mm (9 ³ / ₁₆ ")
Depth	208 mm (8 ³ / ₁₆ ")
Weight	1,2 kg (2,6 lbs)
Approx. 1,8 m (70 ⁷ / ₈ ") cord with 6-pin wall plug.	