


## **DROP AND BLOCK WIRING AT BURIED CABLE TERMINALS**

### **1. GENERAL**

- 1.001** This addendum supplements Section 462-260-207, Issue 2.
- 1.002** This addendum is issued to revise Fig. 2.

### **2. TYPICAL INSTALLATIONS**

- 2.001** The following changes apply to Part 2 of this section:
- (a) Fig. 2—revised



CAPACITY - TERMINAL BLOCKS FOR PC 6/48 AND PC 12/55 CABLE CLOSURES

TYPE OF BLOCK	NOTE	PC 6/48 CLOSURE		PC 12/55 CLOSURE		TERMINAL BLOCKS
		PAIRS TERMINATED (MAX)	NO. OF BLOCKS (MAX)	PAIRS TERMINATED (MAX)	NO. OF BLOCKS (MAX)	
PROTECTED	1 AND 2	12	4	18	6	6A3A-3
PROTECTED	2	12	4	18	6	6A3B-3
UNPROTECTED	2	12	4	18	6	6A2-3
UNPROTECTED	3	12	1	12	1	RPT-12L
UNPROTECTED	3	12	1	12	1	RPT-12
UNPROTECTED	3	13	1	13	1	RPT-13
UNPROTECTED	3	25	1	25	1	RPT-25
UNPROTECTED	3	40	4	40	4	9A1-10
UNPROTECTED	3	50	2	50	2	9A1-25

- NOTES:
- 1. FOR STATION PROTECTION: GROUND CLOSURE TO APPROVED GROUND.
  - 2. USE TERMINAL BLOCKS 6A3A-3 FOR STATION PROTECTION; 6A3B-3 FOR CABLE PROTECTION; AND 6A2-3 WHERE ONLY FUSING PROTECTION IS REQUIRED.
  - 3. THESE BLOCKS ARE USED FOR FIXED COUNT. WHERE TERMINAL BLOCKS ARE NOT REQUIRED, SEE SECTION 631-604-210.

- REFERENCES:
- PC 6/48 AND PC 12/55 CABLE CLOSURE - SECTION 631-604-210;
  - PROTECTION AND GROUNDS - SECTION 460-100-400.

Fig. 2—PC6/48 or PC12/55 Cable Closure—Building Mounted