

Table 2. Characteristics of GTE AE Dials.

CHARACTERISTIC	TYPE								
	24	24A36	51	51A	52	53A	53B	54	154A
Spring Contacts	Single	Single	Single	Bifurcated	Bifurcated	Bifurcated	Bifurcated	Bifurcated	Bifurcated
Pawl Quieting Provision	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Adjustable Spotter Cam (Screw Type)	No	No	No	No	No	No	No	Can Be Adapted	No
Pulse Cam with Scribe Mark (16° or 12°)	No	No	16°	16°	16°	12°	12°	No	12°
Die-Cast Zinc Base	No	No	Yes	Yes	Yes	Yes	Yes	Yes	No
Twin Contact SATT Springs	N/A	N/A	N/A	No	No	Yes	Yes	Yes	No
Separate Bracket Mounting for Impulse and Shunt Springs	Yes	Yes	No	No	No	No	No	No	No
Removable Separate Fingerstop	No	No	No	No	Yes	Yes	Yes	Yes	Yes
Types of Telephones	Type 1A and 34A3	Type 1A, Type 40 and 600 Series	Type 40, 50 and 600 Series 890	Type 40, 50, 83, 183, 95 600, 700, 860A, 880, 881, 882 and 863	Type 80, 85, 86, 87, 80T. 90, 90M 100 and 700 186, 187 102A, 80E, 85EB, and 85ED	Used in SATT A Systems with Type 80, 90, 90M and 100 Series, and 80E	Used in SATT B Systems with Type 80, 90, 90M and 100 Series, and 80E	Type 182, 182A, 192 and SATT Systems	Type 980